

# PSA5184 D/SIDED POLYETHYLENE WHITE FOAM TAPE

## PRODUCT DESCRIPTION :

5184 is a white Polyethylene double sided predominantly closed cell foam tape with a modified acrylic adhesive and a paper release liner.

## DIMENSIONS :

LENGTH : 50M

WIDTH : all sizes available up to 1000mm

THICKNESS : 1 mm & 2mm

## TECHNICAL DATA :

	Typical Value	Units
Adhesive type	Emulsion modified Acrylic	
180 degree peel adhesion	> Internal strength of foam	N/m
Foam density	50	Kg per
cu.m.Shore hardness	53	00 scale
Force to compress by 25%	40	kPa
Liner type	Amber or White Glassine	
Liner release	10	N/m
Tensile strength MD CM	650	kPa
Service temperature	-20 to +120	Deg C
Recommended application Temperature	+5 to +25	Deg C
UV resistance	Excellent	
Fungi resistance	Excellent	
Weather resistance	12	Months

## Application Guidelines :

Surfaces must be clean, dry, free from grease and dirt. Please note manufacturers safety instructions should be followed and customers are recommended to ensure compatibility of the solvent and their substrate. Ideal bonding substrates are those which are: clean, dry, flat, smooth, dust free and non-porous. Low temperatures may increase the risk of condensation, reducing the tack of the product. Life expectancy will vary with temperature and humidity. Product may be applied by hand direct from a roll applying even pressure. The information supplied is accurate to the best of our knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification.

Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss and does not form part of any contract with a customer whatsoever and however arising.