



# Technical Data Sheet

## BACT Cyanoacrylate Activator

### PRODUCT DESCRIPTION

Bondloc Activator is a low viscosity, solvent based cyanoacrylate adhesive activator which contains active components dissolved in a hydrocarbon solvent.

### APPLICATIONS

Bondloc Activator is used to reduce fixing times and ensure that excess adhesive is fully cured. Bondloc activator also reduces blooming and odour. It is particularly useful for production lines such as electronics assembly and UPVC window trim bonding.

### USEFUL NOTES

- Reduces blooming
- Reduces odour
- Fast acting
- Easy to use

### INSTRUCTIONS FOR USE

Spray a small quantity of Bondloc Activator on to one substrate only. Allow solvent to evaporate. Apply cyanoacrylate adhesive to the other substrate and bring together curing will occur almost instantly. Take precautions not

### PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

### CHARACTERISTICS

Chemical base	Hydrocarbon solvent
Appearance	Colourless
Viscosity	1 mPas @ 20°C
Flash point	-60°C
Density	0.79 g/ml
Aerosol Propellant	co2

### STORAGE

Bondloc Activator will have a 12 month minimum shelf life if stored between 5°C and 25°C

### HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS

### PACKAGING FORMAT

Aerosol.....200ml, 400ml

