



Sicad s.p.A.

Via Caduti della Liberazione, 57  
21040 Uboldo (VA) – Italia  
Tel: +39 02 964121 Fax: +39 02 96412294  
Web: www.eurocel.it

## PRODUCT INFORMATION

# EUROCEL PP 5231

### DESCRIPTION

Single sided packaging tape.

### PRODUCT DATA

<b>Backing</b>	0.025 mm BOPP film
<b>Adhesive</b>	Synthetic rubber and resins; transparent, brown

	Unit	Value	Method
<b>Total thickness</b>	mm	0.041	PSTC 133
<b>Adhesion to steel</b>	N/25mm	9	PSTC 101
<b>Tensile strength MD</b>	N/25mm	100	PSTC 131
<b>Elongation at break</b>	%	140	PSTC 131
<b>Temp. Resistance</b>	°C	60°C	=

### APPLICATION

Standard carton sealing tape, suitable for most common use. Low backing thickness version of Eurocel PP 31.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High tack	✓ Performing well in most common use
BOPP backing	✓ Well adaptable to different shapes	✓ Good elongation

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.