

**PRODUCT: 4030**



**PRODUCT DESCRIPTION**

Double-sided self-adhesive tape with cloth carrier, white synthetic rubber based adhesive.

**LINER**

80 gsm yellow/brown two side siliconised paper

**CARRIER**

Cloth

**ADHESIVE**

White synthetic rubber

**MAIN APPLICATIONS**

Suitable for carpet laying, gluing the felt and felt pads, fix heel reinforcements in footwear industrie and lamination of various materials.

**FEATURES**

Adhesive with high tack, moderate shear and high adhesiveness.

**TECHNICAL DATA (average values)**

<b>ELONGATION</b> (AFERA 5004)	<b>[%]</b>	5
<b>TENSILE STRENGTH</b> (AFERA 5004)	<b>[N/cm]</b>	24
<b>180° PEEL</b> (AFERA 5001)	<b>[N/25mm]</b>	>25
<b>STATIC SHEAR</b> (AFERA 5012)	<b>[h]</b>	>3
<b>ROLLING BALL TACK</b> (PSTC 6)	<b>[cm]</b>	<3
<b>THICKNESS</b> (AFERA 5006)	<b>[μ]</b>	250
<b>THICKNESS LINER</b> (AFERA 5006)	<b>[μ]</b>	70
<b>PERFORMING TEMPERATURE</b>	min -10 °C	max +50 °C

**DATE:** 01/09/16

The product has a shelf life of 12 months when stored in original packaging at a temperature of 21 °C with a relative humidity of 50%. BO.MA products were developed based on high quality standards to give good results even in difficult conditions, and are regularly subjected to stringent controls. All information and recommendations contained in our publications are the result of theoretical and practical experiences and provide the best of current knowledge. However, they do not involve any form of guarantee, either direct or implied, regarding the suitability of the product to a particular application, nor can they be considered as a basis for technical specifications. Therefore, determining whether the product BO.MA is appropriate for a specific application or technology is of the user's responsibility. It is therefore advisable to run tests in order to verify the suitability of the tape BO.MA chosen for your application and for the specific performance requirements. BO.MA engineers are always available to help.